

Declaration of Conformity – Ref.No 443180

In compliance with the Construction Products Regulation and The Construction Products (Amendment etc.) (EU Exit) Regulations 2020.

1.	Identification code of product-type	ClassicBoard P3 – 443180
2.	Intended use	Non load-bearing boards for use in humid conditions
3.	Manufacturer	Pfleiderer Deutschland GmbH, Ingolstädter Str. 51, D – 92318 Neumarkt
4.	Authorised representative	not relevant
5.	System of assessment and verification	System 4
6.	Assessment of performance	not relevant
7.	European Technical Assessment	not relevant



8. Declared performance												
Thickness			> 8.9 mm to ≤ 13 mm	> 13 mm to ≤ 20 mm	> 13 mm to ≤ 20 mm	> 20 mm to ≤ 25 mm	> 20 mm to ≤ 25 mm	> 25 mm to ≤ 32 mm	> 25 mm to ≤ 32 mm	> 32 mm to ≤ 40 mm	> 32 mm to ≤ 40 mm	o Harmonised fechnical
Essential characteristics/main features	Unit				De	clared pe	erforman	ce			-	specification
Reaction to fire			D-s2,d0 conforming to EN 13986 dependent on end use (Thickness: ≥ 9 mm / Gross density: ≥ 600 kg/m³) 1									EN 13986:2004
Water vapour permeability, wet cup $\boldsymbol{\mu}$		NPD	15	NPD	15	NPD	15	NPD	15	NPD	15	+A1:2015
Water vapour permeability, dry cup $\boldsymbol{\mu}$		NPD	50	NPD	50	NPD	50	NPD	50	NPD	50	
Class, formaldehyde release		E1 E05										
Release (Content), pentachlorophenol (PCP)	mg/kg	< 3										
Airborne sound insulation (surface mass)		NPD]							
Sound Absorption frequency range 250 Hz to 500 Hz	0.1	J.1										
Sound Absorption frequency range 0.25 1000 Hz to 2000 Hz				5								
Thermal conductivity (density)	W/ (mK)	0.12										
Air permeability		NPD	NPD									
Internal bond	N/ mm²	0.45				0.4		0.35		0.3		
Swelling in thickness, 24 h	%	17		14	-	13			_	12		
Internal bond after boil test			NPD									
 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This Declaration of Conformity is issued under the sole responsibility of the manufacturer identified in point 3. 												
Signed for and on behalf of the manufacturer by:												
Date of issue: 2024-09-17 i. V. Claus Seemann Head of productmanagement core materials (Document was created electronically and is therefore valid without signature!)												
												NPD: performance not defined